



HYDRAULIC 2-POST LIFT

# POWER LIFT HL NT

**THE FAST CLASS**

WITH PATENTED  
**HyperFlow®**  
technology

WITH  
TECHNOLOGY



## THE FIRST CLASS 2-POST LIFT

- ✓ The fastest 2-post lift. Lifting/lowering time: 20 sec/14 sec\*
- ✓ Very low maintenance: no synchronization cables, no pulleys
- ✓ NT and patented HyperFlow® technology: 100% hydraulic, 100% safe
- ✓ A great variety of arms to pick up a wide range of vehicles

**3000 KG | 3500 KG | 4000 KG**

\* For HL 2.30 NT

Made  
in  
Germany

## HYDRAULIC 2-POST LIFT

# POWER LIFT HL NT

## Speed and comfort


The POWER LIFT HL NT features NUSSBAUM's NT and patented HyperFlow® technology: The exceptionally fast lifting time as well as the low maintenance (no cables, no pulleys) will save you time and money. These technologies also guarantee maximum safety. A top quality lift for a safe and efficient workshop!

## Flexible


- ✓ No floor connections
- ✓ No static connection between the columns: Adjustable width (+ 200 mm) and height, flexible height extension from +200 mm up to +900 mm can be provided

## Practical design

- ✓ Precise control with NUSSBAUM commander and lockable main switch. Adjustable lowering speed
- ✓ Oil submerged motor: long lasting and quiet
- ✓ The 4 pulling cylinders are well protected: no risk of damage
- ✓ Compressed air and electric outlet (220V) integrated in the column



## POWER LIFT HL NT: YOUR BEST PARTNER TO LIFT ALMOST EVERY VEHICLE



SC (Sports car arms): extremely flat construction. Very sturdy, made of solid material. Especially suitable for very low and wide sports cars.

NUSSBAUM commander and complete energy set on column with electric outlet and pressurized air. Optional drill holder available

Mini Max lifting arms : easy and c vehicles as well as low clearance v





RECOMMENDED BY  
MERCEDES BENZ  
AND BMW<sup>1</sup>

### VARIABLE HEIGHT

Minimal height of only 3800 mm (version RH), up to 4904 mm with optional column extension

### PRECISE POSITIONING

Smooth operation and variable lowering speed thanks to the NUSSBAUM commander

## POWER LIFT HL NT: different versions suited to your needs

All versions delivered with asymmetric arms for optimum door clearance

- **DT (3 stage arms)**: The short arm has 3 stages, enabling to pick up cars with outer pick-up points (3000 and 3500 kg)
- **Universal (3 stage arms)**: The HL 2.40 NT features 3 stage arms that can reach all pick-up points. From Mercedes SMART to transporters with long wheel base at alternative pick up points (4000 kg)
- **MM (Mini-Max Lifting Arms)**: Ideal for deep drawn side skirt or off-road vehicles.
- **SC (Sports car arms)**: Extremely flat construction. Made of solid steel. Especially suitable for very low and wide sports cars (3500 kg)



## FAST, FASTER, HL NT

- **Lifting and lowering time** 20 seconds / 14 seconds<sup>2</sup>
- **Lower electricity consumption**
- **NT technology**: 4 cylinders and 2 independent hydraulic circuits
- **HyperFlow® technology**: Automatic purging of the hydraulic system, automatic synchronization of the arms in the highest position
- **Less moving parts, less maintenance**



convenient to lift off-road vehicles



## MEASURED FOR SUCCESS

POWER LIFT HL NT	2.30	2.35	2.40
<b>Lifting capacity (kg)</b>	<b>3000</b>	<b>3500</b>	<b>4000</b>
<b>Lifting/lowering time approx. (sec)</b>	<b>20/14</b>	<b>26/14</b>	<b>26/14</b>
<b>Lifting height (mm)</b>	<b>1995</b>	<b>2005</b>	<b>2050</b>
<b>Lowest lifting point (mm) Version DT</b>	<b>95-140</b>	<b>95-140</b>	<b>-</b>
Version MINI-MAX	75-185	75-185	75-185
Version Universal	-	-	115-190
Version SC	-	80-120	-
<b>Total height column (mm)</b>	<b>4022*</b>	<b>4040</b>	<b>4027*</b>
<b>Total height with riser pipe (mm)</b>	<b>4104-4904</b>	<b>4109-4904</b>	<b>4109-4909</b>
<b>Recommended total width (mm) Version DT</b>	<b>3100</b>	<b>3230</b>	<b>-</b>
Version MINI-MAX	3300	3350	3350
Version Universal	-	-	3350
<b>Column distance (mm) Version DT</b>	<b>2560</b>	<b>2646</b>	<b>-</b>
Version MINI-MAX	2760	2846	-
Version Universal	-	-	2766
<b>Arm-extraction long (mm) Version DT</b>	<b>940-1495</b>	<b>940-1495</b>	<b>-</b>
Version MINI-MAX	1000-1480	1000-1480	1130-1840-
Version Universal	-	-	1130-1840
Version BMW	-	940-1495	-
Version SC	-	840-1380	-
<b>Arm-extraction short (mm) Version DT</b>	<b>480-870</b>	<b>570-1160</b>	<b>-</b>
Version MINI-MAX	600-980	600-900	635-1065
Version Universal	-	-	570-1160
Version BMW	-	505-823	-
Version SC	-	590-865	-
<b>Power supply (V/Hz)</b>	<b>400/50/16</b>	<b>400/50/16</b>	<b>400/50/16</b>

\* Version RH with reduced column height of 3800 mm available

DT: 3 stage arms | SC: Extra low "sports car" arms (< 84 mm clearance)

Now also with reduced column height of **only 3800 mm**

Ask for

**HL 2.30 NT RH**  
**HL 2.40 NT RH**

### ACCESSORIES



Height adapter 44 mm



Height adapter 155-245 mm



U-form adapter 150-233 mm



Lashing straps (2 units)



Drive-on tables (4 units)

**More accessories available**

Techn. changes and errors excepted. | Valid from 05 2017 © Otto Nussbaum GmbH & Co. KG | Korker Strasse 24 | 77694 Kehl-Bodersweiler | Germany  
Tel.: +49 (0) 7853 899 - 0 | Fax: +49 (0) 7853 8787 | info@nussbaum-group.de | nussbaum-group.de

**Nussbaum**

NUSSBAUM GROUP is a family owned business from Kehl am Rhein in Germany. For more than 40 years we produce our products exclusively in Germany. Every unit is controlled and thoroughly tested before leaving our facility. We are proud to be one of the world's leading manufacturers of automotive lifts and workshop equipment.



facebook.com/nussbaumgroup



youtube.com/nussbaumgroup

**Made  
in  
Germany**