



**Lifting Height - 78.75"**  
Can be installed above ground or recessed in floor

**Adjustable Platform**  
Easy, safe and flexible extending platform that allows it to pick up a wide range of vehicles

**Low drive-on height and installation depth**

**Stability**  
High quality steel construction



**Increased Productivity**  
No mechanical connection between the platforms allows free access between the scissors

**Operating Safety**  
Robust oil-submerged motor with push button control

NUSSBAUM NT hydraulic system provides steady and smooth starting and stopping

Redundant hydraulic safety

**JUMBO NT - like lifting with two lifts**

### Function & Safety

Two independent hydraulic circuits ensure safe and smooth lifting of the scissors. The fully hydraulic system requires no electrical or pneumatic components. A compact oil-submerged motor controls the JUMBO LIFT NT.



The JUMBO is a double-scissor lift with optional lifting capacities of 7,000 & 9,000 pounds. It is the perfect lift for car inspection, tire service, fast repair, dealerships and service centers. It allows workshops to increase productivity through improved utilization of space. From a business performance perspective, the JUMBO LIFT is the most cost effective solution on the market.



JUMBO – easy to use extending platforms lift a wide range of vehicles



Push Button Controls



High Density Polymer Pads

## JUMBO FEATURES:

- Double-Scissor Lift
- Low profile (4") is ideal for low clearance vehicles
- Adjustable lifting platform length from 57.5" up to 81"
- Install above ground or recessed in floor
- Fast installation and setup
- Free passage between the scissors
- Maximum utilization of workshop space
- Perfect for low ceiling or narrow bay applications
- Fully hydraulic system
- Compact oil-submerged motor
- Push button controls
- No electrical or pneumatic components
- Fast and safe pick-up of the vehicle through use of high density polymer pads
- Fast lifting and lowering times

Technical Data*	7000	9000
Lifting Capacity (lbs)	7,000	9,000
Lifting Time Approx. (sec)	36	35
Lifting Height (in)	79"	79"
Drive Over Height (in)	4"	5"
Total Width (in)	79.5"	79.5"
Lifting Platform Width (in)	24"	24"
Lifting Platform Length (in)	57.5" - 81"	57.5" - 81"
Motor (hp)	3,0	3,0
Power Supply	208/230 / 1ph / 20 AMP	208/230 / 1ph / 20 AMP

Accessories	7000	9000
Rubber truncated pyramid pad	•	•
Polymer Pad 2"	•	•
Polymer Pad 4"	•	•
Side Ramps for Narrow Installation	•	•

\* All technical data are subject to change.