


4.55 SL

Automotive Lift date: 01/2010
Manual Date: 02.01.2010



Original Operating Instruction

Operating Instruction and Documentation

Serial-number:.....

Retailer address / phone

Made in Germany



Nussbaum

Otto Nußbaum GmbH & Co.KG • Korker Straße 24 • D-77694 Kehl-Bodersweier
Tel: +49(0)7853/8990 • Fax: +49(0)7853/8787
E-mail: info@nussbaum-lifts.de • <http://www.nussbaum-lifts.de>

Content

Foreword	3
Record of installation	5
Record of handing over	6
1. General Information	7
1.1 Installation and service checks of the automotive lift	7
1.2 Warning Symbols	7
2. Master document of the automotive lift.....	8
2.1 Lift–manufacturer.....	8
2.2 Application	8
2.3 Changes at the construction	8
2.4 Displacement of the automotive-lift.....	8
2.5 Declaration of conformity	9
3. Technical Information	10
3.1 Technical ratings	10
3.2 Safety device	10
3.3 Data sheet	11
4. Safety regulations	12
5. Operating instructions	13
5.1 Lifting the vehicle	13
5.2 Synchronism of the automotive lift.....	13
5.3 Lowering the vehicle	14
6. Troubleshooting	14
6.1 Emergency lowering	15
6.2 Driving onto an obstacle	16
6.3 Function of safety device	16
6.4 Manually equalisation of the carriage	16
6.5 Driving to the Reference point	17
7. Inspection and Maintenance.....	18
7.1 Maintenance plan of the lift.....	19
7.2 How often must the lift be cleaned?.....	22
7.3 Adjust the Polylex-belt	23
7.4 Examine the carrying nut system.....	24
7.5 Examine of the stability of the automotive lift.....	25
8. Installation and Initiation	25
8.1 Regulations.....	25
8.1.1 Erection and doweling of the lift.....	26
8.2 Initiation	27
8.3 Change of lift location	27
8.4 Key in the reference point with the keyboard.....	28
9. Security check	30
First security check before installation.....	35
Regular security check and maintenance	36
Regular security check and maintenance	37
Extraordinary security check.....	43
Electrical diagram	44
Spare parts	68

Foreword

Nußbaum lifting systems are the result of over 25 years experience in the automotive lifting industry. The high quality and the superior concept ensure reliability, a long lift lifetime and above all an economic business solution.

To avoid unnecessary damage, injury or even death, read the operating instructions with care and observe the contents.

Nußbaum lifts is not responsible for incidents involving the use of Nußbaum lifting systems for applications other than those for which they were designed.

Nußbaum GmbH & Co. KG is not liable for any resulting damages. The user carries the risk alone.

Obligations of the user:

- To observe and adhere to the operating instructions.
- To follow the recommended inspection and maintenance procedures and carry out the prescribed tests.
- The operating instructions must be observed by all persons working with or around the lift.
- Above all chapter 4 "Safety Regulations" is very important and must be closely adhered to.
- In addition to the safety regulations stated in the operating instructions manual, the appropriate safety regulations and the operating procedures of the place of operation must also be considered.

Obligations of the operator:

The operator is obliged to allow only those persons complying to the following requirements to work with or around the unit.

- Persons being familiar with the basic regulations concerning labour safety and accident prevention and being trained to operate the particular unit.
- Persons having read and understood the chapter concerning safety and warning symbols.
- Persons using the lift are required to confirm that they have read and understood the chapter on safety and warning symbols by signing the appropriate form.

Dangers when operating the lift:

Nußbaum-Lifts are designed and built according to technical standards and the approved regulations for technical safety. The use of Nußbaum lifts for purposes other than those for which they were designed, may result in injury or even death.

The lift must only be operated :

- For its appropriate use
- In faultless condition concerning technical security.

Organisational Requirements

- The instructions for use are to be kept at the place of operation being easily accessible at any time.
- In addition to the instructions for use, rules pertaining to other regulations i.e. accident prevention and environmental rules are to be observed and adhered to.
- The owner of the Nußbaum lifting system must ensure that operators and persons working with or around the lift occasionally conduct "refresher" courses to ensure that the appropriate operating procedures and safety precautions are known.
- Personal Protective Equipment (PPE) must be used according to the appropriate regulations.
- All safety- and danger signs on and around the lift are to be observed and followed!
- Spare parts must comply with the technical requirements specified by the manufacturer.
This is only warranted with original parts.
- Observe and adhere to the specified time intervals between tests and inspections.

Maintenance works, repairing faults

- Adjustments, maintenance, and inspections, are to be followed according to the time intervals specified. Details regarding the exchange of parts and components as mentioned in the operating instructions are to be adhered to.
These works must only be carried out by expert personal.
- After maintenance- and repair works loose screws, nuts and bolts must always be firmly tightened!

Guarantee and liability

- Our "General conditions of selling and delivering" are in force.
There will be no guarantee or liability for incidents involving injuries or death or damage to equipment if these incidents are the result of one or more of the following reasons.
- Inappropriate use of the lift
- Inappropriate installation, initiation, operation and maintenance of the lift.
- Use of the lift while one or several security devices do not work, do not work correctly or are not installed correctly.
- Failure to follow the regulations of the operating instructions regarding transport, storage, installation, initiation, operation and maintenance of the lift.
- Unauthorized changes to the structure of the lift without first asking the producer.
- Unauthorized changes of adjustments of important components of the lift (e.g. driving elements, power rating, motor speed, etc)
- Wrong or incorrect maintenance practice.
- Catastrophes, acts of God or external reasons.



After completely filling out this sheet including signatures, copy and return the original to the manufacturer. The copy must remain in the manual.

Otto Nußbaum GmbH & Co. KG
Korker Straße 24
D-77694 Kehl-Bodersweier

Record of installation

The automotive lift with the

serial number:..... was installed on:.....

at the firm:..... at:.....

The initial safety check was carried out and the lift was started.

The installation was carried out by the operating authority/competent (please delete as applicable).

The initial safety check was carried out by a competent person before the initial operation.

The operating authority confirms the correct installation of the automotive lift, the competent person confirms the correct initial operation.

Used Dowels(*):_____ (Type/Name)

Minimum anchorage depth (*) kept: _____ mm ok

Starting torque (*) kept: _____ NM ok

..... date name of the operating authority signature of the operating authority

..... date name of the competent person signature of the competent person

Your customer service:..... (stamp)

(*) see supplement of the dowel manufacturers

Record of handing over

The automotive lift with the

serial number:..... was installed on:.....

at the firm:..... at:.....

the safety was checked and the lift was started.

The persons below were introduced after the installation of the automotive lift. The introduction was carried out by either the erector from the lift-manufacturer or from a franchised dealer (competent person).

..... date name signature

..... date name of competent signature of the competent

Your customer service:.....(stamp)

1. General Information

The document “**Operating Instructions and Documentation**” contains important information about installation, operation and maintenance of the automotive lift.

- Conformation of **installation of the automotive lift** is recorded on the "Record of Installation" form and must be signed and returned to the manufacturer.
- Conformation of once of, regular and out of the ordinary service checks is recorded in the respective check forms. The forms are used to document the checks. They should not be removed from the manual.
- All **Changes to the structure** and any change of **location** of the automotive lift must be registered in the "**Master document**" of the lift

1.1 Installation and service checks of the automotive lift

Only specialised staff are allowed to repair and maintain the lift and only these specialised staff are allowed to conduct safety checks on the lift. For the purposes of this document these specialised staff will be called Experts and Competent persons.

Experts are persons (for example self-employed engineers, experts) which have received instructions and have the appropriate experience to check and to test the automotive lifts. They are aware of the work involved and know the accident prevention regulations.

Competent persons are persons who have acquired adequate knowledge and experience with automotive lifts. They have completed the appropriate training provided by the lift-manufacturer (the servicing technicians of the manufacturer or dealer, are regarded as competent)

1.2 Warning Symbols

The three symbols below are used to indicate danger and other important information. Pay attention to areas on and around the lift that are marked with these symbols.



Danger! This sign indicates danger. Ignoring this warning may result in injury or even death.



Caution! This sign cautions against possible damage to the automotive lift or other material objects in the case of improper use .



Attention! This sign indicates an important function or other important information regarding the operation of the lift.

2. Master document of the automotive lift

2.1 Lift-manufacturer

Otto Nußbaum GmbH & Co.KG
Korker Strasse 24
D-77694 Kehl-Bodersweier

2.2 Application

The automotive lift is a lifting mechanism for lifting motor vehicles with a laden weight of up to 5500 kg . The max. load distribution is 2:1 either in or against the drive-on direction.

The automotive lift has been designed for servicing vehicles only. It has not been designed to carry people. Carrying people either directly on the lift or in vehicles that are on the lift is therefore not allowed.

The installation of the standard lift in hazardous or dangerous locations such as wash bays is dangerous and is therefore not allowed.

Changes of construction, repairing and changes of place must be registered in this master document.

2.3 Changes at the construction

**Changes at the construction, expert checking, resumption of work
(date, kind of change, signature of the expert)**

name, address of the expert

place, date

signature of the expert

2.4 Displacement of the automotive-lift

**Displacement of the automotive-lift, expert checking, resumption of work
(date, kind of change, signature of the competent)**

name, address of the competent

.....
place, date

.....
signature of the competent

2.5 Declaration of conformity**EG- Konformitätserklärung****Nussbaum**

gemäß Maschinenrichtlinie Anhang II 1A

Declaration of Conformity according Machinery Directive 2006/42/EG ANNEX II 1A
Déclaration de conformité selon directive machines annexe II 1A
Declaración de conformidad según Directiva Maquinaria 2006/42/EG ANNEX II 1A
Dichiarazione di conformità in accordo alla direttiva 2006/42/EG ANNEX II 1A

Hiermit erklären wir, daß die Hebebühne, Modell:

Hereby we declare that the lift model:

Par la présente nous déclarons que le pont élévateur modèle:

Por la presente declara, que el elevador modelo:

Con la presente si dichiara che il sollevatore:

COMBI LIFT

COMBI LIFT 4.50 SL A MB

COMBI LIFT 4.55 SL

allen einschlägigen Bestimmungen der folgenden Richtlinien entspricht:

fulfills all the relevant provisions of the following Directives:

correspond aux normes suivantes:

cumple todas las disposiciones pertinentes de las Directivas siguientes:


adempie a tutte le richieste delle seguenti direttive:

Maschinenrichtlinie / Machinery Directive
EMV Richtlinie / EMC Directive2006/42/EG
2004/108/EGin Übereinstimmung mit den folgenden harmonisierten Normen gefertigt wurde
was manufactured in conformity with the harmonized norms
fabriqué en conformité selon les normes harmonisées en vigueur.
producido de acuerdo a las siguientes normas armonizadas.
è stato fabbricato in conformità con le norme armonizzateFahrzeug- Hebebühnen / Vehicle lifts
Elektromagnetische Verträglichkeit / Electromagnetic compatibility (EMC)EN 1493: 2010
EN 61000-6-2 , -6-4Beauftragter für die Technische Dokumentation
Authorised to compile the technical file

Otto Nußbaum GmbH & Co. KG

Seriennummer
Serial number-----
Seriennummer

Kehl- Bodersweier, 12.03.2012


Hans Nußbaum

3. Technical Information

3.1 Technical ratings

Capacity:	5500 kg
Load distribution:	max. 2:1 in or against the drive on direction
Lifting time:	approx. 40 sec.
Lowering time:	approx. 40 sec.
Line Voltage:	3~/N+PE, 400 Volt ,50 Hz
Power rating:	4 x 1,5 kW
Motor rotation:	1420 rotation/Min
Sound level L _{pA} :	≤ 70 dB(A)
Connection by customer	3~/N+PE, 400V, 50 Hz fuse 32 Ampere (time-lag fuse) observe your regulations of your country
Optional: Energy set:	Pneumatic connection: air pressure 6-10 bar Electrical plug: 220V/50hz



3.2 Safety device

1. Safety switching in case the carrying nut breaks
Examination of the carrying nut with a wear-pin into the lifting carriage.
2. Electronic disconnection
If the final position is reached, the lifting platform switched-off
3. Electronic synchronisation
Safety device against unequal run of the lifting carriage
4. Safety catch hook
Safety device against repeated raising if the lifting nut is broken
5. Roll over safety device at the end of the platform
Safety device against falling down
6. Totmann" control
After let go of the buttons, the current movement of the lift stops
Optional:
7. foot protection
Safety device to avoid crushing
8. CE-STOP + acoustic signal
Safety device to avoid crushing

3.3 Data sheet

Wir weisen in unseren Plänen auf die Mindestanforderungen des Fundaments hin, jedoch der Zustand der örtlichen Gegebenheiten (z.B. Untergrund) liegt nicht in unserer Verantwortung. Im Bedarfsfall ist es ein Architekt, Statiker und Bauunternehmer zu kontaktieren.

We point out the minimum requirement of the foundation in our plans. The condition of the local realities (for example: ground under the foundation does not lie in our responsibility) necessitate an architect must be consulted.



Bouselits an der Bediensoule bereitstellen:
 Netzanschluß: 3PH N+PE: 400V 50Hz
 Absicherung: 32Ampere triptag
 Druckluft: lichte Weite 6mm. 6-10 bar (für opt. lanzen Jack)
 prepared by customer at the operating column:
 power supply: 3PH, N+PE, 50Hz
 Fuse: 32 Ampere time lag
 Air pressure: inner diameter 6mm, 6-10 bar
 (for pneumatic slot and for optional lock)

Eigengewicht
down weight:
ca. 3500kg

All dimensions in millimeter
subject to alterations!

Rechnungsnummer
450SL20020

4. Safety regulations

If you use the automotive lift, the German following regulations are to be considered:
BGG945: Examine of automotive-lifts; BGR500 Using automotive-lifts; (VBG14).

Especially the following regulations are very important:

- The laden weight of the lifted vehicle must not exceed 5500 kg for the automotive lift.
Load distribution max. 2:1 in or against the drive on direction.
- While working with the lift the operating instructions must be followed.
- The automotive lift must be in its lowest position (fully collapsed), before the vehicle can be driving on to the lift. Only then can the vehicle be lifted.
- Vehicles with low clearance or vehicles that are specially equipped should be pre tested to ensure that they clear the lift ramp to avoid damage.
- Only trained personnel over the age of 18 years old are to operate this lift. (see data sheet "Record of handing over")
- No one is to stand within the working area (danger area) during lifting and lowering.
- No one is to be raised or lowered either directly or in a vehicle by the automotive lift.
- No one is to climb onto the automotive lift or onto an already raised vehicle.
- The automotive column lift must be checked by an expert after changes in the construction have been made.
- Position the rubber pads at the pick-up points under the vehicle as described of the vehicle manufacturer. (optional: version with Jack)
- Observe the complete lifting and lowering procedure.
- It is not allowed to install the lift in hazardous or dangerous locations (outdoor, washing bays).
- The main switch must be switched off and locked before work on the vehicle can commence. This is a safety precaution to ensure that the lift does not move during work.
- The main switch must be switched off and locked before any maintenance or repair work on the automotive lift itself can be carried out.

5. Operating instructions



The Safety Regulations must be observed and adhered to while working with the automotive lift. Read the safety regulations in chapter 4 carefully before working with the lift!

5.1 Lifting the vehicle

- Drive the vehicle onto the middle of the lift.

The complete wheels must be standing on the platform, otherwise the vehicle can fall down.



- Secure the vehicle against rolling, put into gear, apply the hand brake.
- Control the dangerous places of the lift and be sure that there are no objects or people in the immediate area of the lift or on the lift.
- Switch on the main switch. Raise the vehicle Press the button „Lifting“.
- Raise the vehicle to the required working height. Press the button “lifting“ .
- The roll over and roll back safe device must be activated when the lift was slightly raised.
- Observe the complete process.



Check the safe position of the vehicle on the platform.



The automotive-lift can regulate several times depending upon distribution of the load.



pic: operating elements

- 1 Main switch
- 2 Keyboard and LC-Display
- 3 Button „Lifting“
- 4 Button „Lowering“
- 5 Button „Equalisation“
- 6 Red light „Malfunction“
- 7 Switch „Lighting“ (optional)

5.2 Synchronism of the automotive lift

- The lift is equipped with an electronic synchronism.
- At the columns are potentiometer which recognizes the actual-position of the spindle.
- A lifting carriage is faster like the other lifting carriage. No matter whether when lifting or lowering. The electronic control system observe this procedure and stops the fastest carriage so long until all carriage have the same height again. The permitted regulation range is 18 mm.

5.3 Lowering the vehicle

- Control the dangerous places of the lift and be sure that there are no objects or people in the immediate area of the lift or on the lift.
- Before the lift reaches its lowest position, the lift stops automatically (CE-Stop). After the lift has stopped, check the danger area around the lift. Press the button "lowering". An acoustic signal will sound as the lift is further lowered. This is to warn against the risk of crushing as the lift is slowly lowered to its lowest position.
- Drive the vehicle in to the working height or to the lowest position.



The automotive-lift can regulate several times depending upon distribution of the load.

- Drive the vehicle from the platform.
- Observe the complete process.

6. Troubleshooting

If the lift does not work properly, the reason might be quite simple. Please check the lift for the potential reasons mentioned on the following pages. If the cause of trouble still cannot be found, please call technical service.

Self-employer repair-working is prohibited.



Repairs at the security devices of the lift as well as repairs and examinations of the electrical fittings are forbidden.

Repairs at electrical system may be accomplished only by expert persons.

Problem: The lift does not lifting and not lowering!	
<u>possible causes:</u>	<u>remedyng:</u>
No electrical power supply	Examine the power supply
The main switch is not switched on	Examine the main switch
Press button „lifting“ is defective	Examine the press button
The fuse is faulty	Examine the fuse, replace it if necessary
The feed line is cut	Examine the feed line
The motor is overheated	Let it cool down
The plug connection between the motors are loose	Examine the plugs
The lift is not in the regulation range	Equalize manually (see chapter 6.4)
V-Belt is torn or defective	Shut down the lift. Replace the V-belt and adjust it again (see chapter 7.3)

<i>Motor defective</i>	<i>Make an emergency lowering (see chapter 6.1)</i>
<i>Battery on the control board is empty. The lift drive out of the synchronism window</i>	<i>Phone the service partner</i>

Problem: The lift does not lifting!

<u>possible causes:</u>	<u>remedyng:</u>
<i>Only 2 phases active</i>	<i>Examine by an electrician</i>
<i>V-Belt is torn or slack</i>	<i>Shut down the lift. Replace the V-belt and adjust it again (see chapter 7.3)</i>
<i>The lifting nut is broken, the safety device(catch hook) is active, the lift is not in the regulation range and the lift has switched off</i>	<i>Shut down the lift and phone the service partner</i>
<i>Top limit switch is active</i>	<i>Only lowering procedure is possible</i>

Problem: The lift does not lowering!

<u>possible causes:</u>	<u>remedyng:</u>
<i>the bottom limit switch is active</i>	<i>Only lifting procedure is possible</i>
<i>The lifting carriage or a platform is driven on a obstacle</i>	<i>Equalise the lift manually</i>
<i>V-Belt is torn or slack</i>	<i>Shut down the lift. Replace the V-belt and adjust it again (see chapter 7.3)</i>

6.1 Emergency lowering

In case of power failure the lift can not lowered with the motors. In this case there is the possibility to lower the lift manually. Switch off the main switch and lock it. Remove all four cover of the v-belt pulleys. Turn alternately (5cm) the nuts on the top end of the spindle anticlockwise until the lift is in the lowest position. After it, remove the vehicle.



The emergency lowering must only carried out by persons which are instructed to using the lift. Please refer to the regulation "Lowering the vehicle".

Procedure the emergency lowering

- Switch off the main switch and lock it.
- Remove all four cover of the v-belt pulleys.
- Turn alternately (5cm) the nuts on the top end of the spindle anticlockwise until the lift is in the lowest position. After it, remove the vehicle.

In case of disturbance or defect, secure the lift against authorized person. Phone your service partner.

6.2 Driving onto an obstacle

If the platform or the lifting carriage is lowering on an obstacle, the motor from this side will be locked. The lift switched off if the lifting carriage are not more in the regulation range (approx. 50 mm).

An additional protection is the temperature control system in the motor. It interrupt the electrical circuit when it is overloaded. You can not work with the lift. Cool down approx. 5 – 10 min. dependently on the outside temperature.

After the locking of the motor, examine the V-belt, if necessary exchange it. Call your service-partner.

6.3 Function of safety device

The lift is equipped with a safety switching, which controls the wear of the main nut. If the lifting nut is broken, a safety nut which is conducted loose in the spindle, carries the load. After a break of the nut, the lift can only once being lowered in the lowest position. If the lift has reached the lowest position it is not possible to raise the lift again. The lifting carriage of the broken side gets mechanically locked. During the lifting the other side is driving out of the regulation range and switched off the lift. You can not work with the lift anymore. Call the service-partner.



If the safety device is active, Shut down the lift and phone your the service partner!



Switch off the main switch at all repairs and disturbances!



The electrical system may only be opened by trained persons!

6.4 Manually equalisation of the carriage


The lift is equipped with a position measuring system which guarantee the synchronisation of the lift. The electrical control recognises if one lifting carriage is approx. 20 mm earlier at the definite height. The electrical control stopped the motor of this carriage until both carriage have the same height again. After it both motors are working together again.

If the carriages of the lift are driving out of the regulation range/switiching off window of approx. 5 0mm), the electrical control recognises this and switched off the lift.

To reach the normal function of the lift you must equal manually the carriages. Remove the cover of the V-Belt pulley at the top of the lift. Equal the lift: turn the nuts until the carriages have the same height.

- Carry out the equalisation with the lift only without load.
- Open the electrical box.
- See the DIP-switches on the controller (Pos.2).

Pic 4: DIP-switches on the board.



Only trained and authorized staff is allowed to work with the DIP-switches! The main-switch has to be switched off!

- DIP switch 5 (regulation ON/OFF)
- DIP switch 1 (only column 1 moveable)
- DIP switch 2 (only column 1 moveable)
- DIP switch 3 (only column 1 moveable)
- DIP switch 4 (only column 1 moveable)

example: Equal the column 1:

- Equalization the column 1 as follows:
- Move the DIP switch 5 on position "off" (regulation off)
- Move the DIP switch 1 on Position „ON“ (DIP switch 1 for column 1)
- Press the button „lifting“ or „lowering“ until the column has the same height as the other columns.
- Move the DIP switch 1 on position „off“.
- Move the DIP switch 5 on position „on“ (regulation on).
- If necessary repeat the procedure with the column 2,3 and 4 until all columns (lifting carriage are on the same height.
- Close the electrical box.

6.5 Driving to the Reference point

After 50 working steps shows the display „Referenzpunkt anfahren“ (Drive to the reference point). Now, it is necessary to drive the lift to the reference point, because the height of the carriage can be examined.

This can be achieved by a variety of factors sturgeon (dirt, slack, interference pulses, etc.)

- Lower the lift into the lowest position
- Drive the vehicle from the platform

- Open the electrical box.
- Press the button (see pic 5) and hold it pressed and press simultaneously the button „lifting“ until the lift stops at the reference point. Turn off the main switch.



pic 5: button „reference point“

The reference point is marked at every column. Examine the points with the carriage. In case the level of the carriage and the reference point is not on the same height, level out manually the carriage at the spindle until the level is ok. In this case the main switch must be turned off.

Remove the cover at the top of the columns and turn the spindle with a suitable tool until the carriage is on the „reference point“.

***switch power back and push on the keypad # enter 1234 and #, with the * go to menu point "reference point" and enter # now confirm with # again.
push * several times to get to the menu point "return" and confirm with # finished.***

7. Inspection and Maintenance



Before conducting maintenance work, preparations must be made to ensure that during maintenance and repair work there is no risk to the safety of people working on or around the lift and also that there is no risk of damage to equipment being used on or around the lift.



German legal guidelines : BSV (Prescription of working tools) + BGR500 (Work with working tools)

To guarantee the utmost availability and to ensure that the lift remains functional, maintenance work contracts are organised between our clients and their local retailers.

A service must be performed at regular intervals of 3 months through the operator in accordance with following service manual. If the lift is in continuous operation or in a dirty environment, the maintenance rate must be increased.



During daily operation the lift must be closely observed to ensure that it is functioning correctly. In the case of malfunction or leakage the technical service must be informed.

7.1 Maintenance plan of the lift



Before beginning any maintenance work isolate the power supply. Secure the main switch (lock it). Secure the danger area around the automotive lift and secure the lift against unintentional lowering.

Maintenance plan	period
Check the condition of the type plate, sticker, short operating instruction. Clean it and if necessary replace it.	Daily
Grease the lubricate nipples with a multipurpose lipid. (example: Auto Top 2000 LTD. Agip). Before remove the spindle cover . Avoid too much grease.	min. once in a year
Check condition the Poly-V belt. and if necessary replace it. Observe the chapter of the V-Belt installation.	min. once in a year
Check the spindle for wear.	min. once in a year
Oiling the spindle and the lubricating felt between the carrying nut and the centring of the spindle one time a month with a thin oil as SAE15W40. Attaching twice lifting and lowering the lift in the end position. After lifting and lowering the lift with load. The lubricating interval has to be carried out at every maintenance. If the lift is in continuous operation, the maintenance rate has to be increased. The nut between the column and the covering will greased with an oil can. The regular complete lubrication in the mentioned distances secures the absolutely easy operation for the lift. <i>Do not use adhesive Oil. A formation of resin is possible and a damage can occur. Normal adhesive Oil impaired the running of the lift negative. We recommended e.g. SAE 15W40.</i>	nach der Montage and min. once in a year
	carrying nut (optical wearing device). To check the carrying nut, take off the covering of the spindle. There is a pin built in the carrying plate. This pin must be even with the top edge of the carrying plate (upper side of the lifting carriage; built-in state. If the pin looks 2 mm out of the top edge at the annually check (changing state). The carrying nut and the sequence nut must be replaced.

   <p>Please, do not sawing the plastic parts <u>only filing!</u></p>	<p>Examine the condition and the function of the spindle centering (after running delay) annually, or if necessary. Adjust it, if necessary or handle it with a file. Is it not possible to adjust the spindle centering anymore, exchange it.</p> <p>Examine the spindle centering without a torque moment key: (4 Nm) Gap: approx. 1mm Back: the half shells touch with the back</p> <p>Switch off the main switch. Take one hand on the spindle and rotate it easily back and forth. During this procedure, fasten the hose clamp with a suitable tool until the back and forth movements are only possible with more power. In this case put the second hand on the spindle, too. The spindle centering is correctly fastened, when the spindle can be rotated with the two hands but with more expenditure of force.</p> <p>Before starting another maintenance, carry out the same procedure at the second column.</p> <p>In case the spindle can be easily moving despite fastening the spindle centering, then it is necessary to work at the cut edge of the spindle centering. Or exchange the spindle centering if necessary.</p> <p>Note: After the repair, both lifting carriage must be on the same level. If necessary, adjust the spindle with the hand. (see chapter 6.4 in the detailed documentation).</p>	min. once in a year
Check the condition and function of the roll back safety device at the end of the platforms	min. once in a year	
Check the condition and function of the flat plates, platforms. In case of damages exchange defective parts.		
Check the Spindle DU-bearing (below) of wear. Oil it with e.g. an SAE 15W40.	min. once in a year	
Check the condition and function of the sliding plates. Remove the cover and clean the frame. Lubricate the balls	min. once in a year	
Check the condition and function of the CE-Stop and acoustic signal	daily	
Check the condition and function of the electrical press button	daily	
Grease the lubricate nipples of the slave nuts (behind the spindle cover) with a multipurpose fat. (example: Auto Top 2000 LTD. Agip). Remove the spindle cover and lubricate the nut through the bore hole of the lifting carriage. Avoid too much grease.	monthly	
Check the condition and the function of the sliding blocks of the lifting carriage and also the sliding surfaces of the columns. After cleaning lubricate it.	min. once in a year	

Alle Befestigungsschrauben und Befestigungsdübel sind mit einem Drehmomentschlüssel zu prüfen.

Anzugsdrehmoment (Nm) für Schraubensysteme

Festigkeitsklasse 8.8

	0,10*	0,15**	0,20***
M8	20	25	30
M10	40	50	60
M12	69	87	105
M16	170	220	260
M20	340	430	520
M24	590	740	890

Festigkeitsklasse 10.9

	0,10*	0,15**	0,20***
M8	30	37	44
M10	59	73	87
M12	100	125	151
M16	250	315	380
M20	490	615	740
M24	840	1050	1250

* Gleitreibungszahl 0,10 für sehr gute Oberfläche, geschmiert

** Gleitreibungszahl 0,15 für gute Oberfläche, geschmiert oder trocken

*** Gleitreibungszahl 0,20 Oberfläche schwarz oder phosphatiert, trocken

min. once in a year

Drehmomentschlüssel 8.8 (G)

Alle Schweißnähte sind einer Sichtprüfung zu unterziehen. Bei Rissen oder Brüchen von Schweißnähten ist die Hebebühne stillzulegen und ihr Händler zu kontaktieren.

min. once in a year

Check the varnish:

Damage to external surfaces, must be immediately repaired.

If these repairs are not made immediately, permanent damage to the powder-coated surface may result.

Repair and clean damaged areas with an abrasive paper (grain 120). After this is complete, use a suitable paint (observe the RAL Number).

Check the zinc surface and repair it with a suitable tool. Use abrasive paper (grain 280).

White rust can result from moisture laying in certain areas for long periods of time. Poor aerating can also result in rust formation.

Rust may result from mechanical damage, wear, aggressive sediments (de-icing salt, liquids) or insufficient cleaning.

Repair and clean these areas with abrasive paper (grain 280).

After this is complete, use a suitable paint (observe the RAL Number).

min. once in a year

Check the condition and function of the electrical parts:

- plugs

- During the installation and the maintenance, check the condition of the electrical cables. The cables and wires must be secured, that they are not crushed or kinked, and that they no touched rotating components (e.g. V-belt pulley contact, etc.).

min. once in a year

Check the condition and function the optional Energy set:

- plug and fuse
- pneumatic connection

min. once in a year

Check the condition and function of the optional lighting

min. once in a year

Check the condition and function of the optional Jack.
Chassis, pneumatic lines, connection

min. once in a year

Check the condition and function cable cannel. Exchange defective parts.

min. once in a year

Check all welded joints for cracks on the automotive-lift.

If any cracks are found on the lift cease use immediately. Switch-off and secure the main switch (lock) and call the service partner.

min. once in a year

Check that all screws and bolts are fasten correctly with torque (turning moments, see the list)

min. once in a year

Turning moment for screws

property class 8.8

	0,10*	0,15**	0,20***
M8	20	25	30
M10	40	50	60
M12	69	87	105
M16	170	220	260
M20	340	430	520
M24	590	740	890

Drehmomenttafel 8.8-10.9 E

property class 10.9

	0,10*	0,15**	0,20***
M8	30	37	44
M10	59	73	87
M12	100	125	151
M16	250	315	380
M20	490	615	740
M24	840	1050	1250

- * sliding friction 0,10 for very good surfaces, lubricated
- ** sliding friction 0,15 for good surfaces, lubricated oder dry
- *** sliding friction 0,20 surface black or phosphatized, dry

7.2 How often must the lift be cleaned?

A regular and appropriate maintenance practice will aid the preservation of the lift.

No guarantees can be given when damage (egg rust or fading colour) is the direct result of poor maintenance and cleaning practice.

Regular cleaning of all kinds of dirt is the best protection against wear and the formation of rust and will prolong the life of the lift

- Dirty deposits that can cause rust include:

- de-icing salt
- sand, pebble stone, natural soil
- all types of industrial dust
- water; also in connection with other environmental influences
- all types of aggressive deposits
- constant humidity caused by insufficient ventilation

Obviously this is dependent on the type of work being done with the lift, the degree of cleanliness of the workshop and location of the lift. The degree and amount of dirt is dependent on the season, on the weather conditions and the ventilation of the workshop.


During poor conditions it may be necessary to clean the lift once week, but cleaning once a month will suffice.

Clean the lift and the floor with a non-aggressive and non-abrasive detergent. Use a gentle detergent to clean the parts. Use a standard washing-up liquid and lukewarm water.

- Do not use steam jet cleaners.
- Remove all dirt carefully with a sponge or if necessary with a brush.
- Ensure that no washing-up liquid is left on the lift after cleaning.
- Do not use aggressive means for cleaning the workshop floor and the automotive lift.
- A permanent contact with any kind of liquid is not allowed. Do not use high pressure devices for cleaning the lift.
- After cleaning dry the automotive-lift with a suitable type of cloth and inject it with a wax spray or an oil spray.

7.3 Adjust the Polylex-belt

If the V-belt was exchanged, the V-belt must be adjusted, again. Remove the cover of the V-belt.



pic 10: cover of the belt (version with raising pipe)


1: column

2: raising pipe

3: cover of the belt

4: spindle

The new V-belt tension must be adjusted at the stretch device. (pic.11). Loose the three screws at the motor easily. (pic. 11, No.1). The belt can be loosened or tightened at the screws. (pic.11, No.2).



pic 11: position of the belt


1: raising pipe

2: stretch device

3: V-belt pulley

4: Polyflex-belt

5: shaft of the motor



pic 12: adjust the belt tension



1: the three screws of the motor

2: adjusting screws



pic 13: accessory

- Put the device on a solid flat surface. Push it down until the pin is on the flat surface. Position the clock on zero. Turn the ring of the clock so long until the indicators are on zero. Put the device on the V-belt (pic.14,15). The indicator of the clock may only turn mini. 1 (1mm) until 1,5 (1,5mm) turn.




- Bring the screws back in initial position.

7.4 Examine the carrying nut system

- Carrying nut (optical wearing device). To check the carrying nut, take off the covering of the spindle (pic.3, pos.b). There is a pin built in the carrying plate (pic.16). This pin must be even with the top edge of the carrying plate (upper side of the lifting carriage; built-in state pic.17). If the pin looks 2 mm out of the top edge at the annually check (pic.17 changing state). The carrying nut and the sequence nut must be replaced.






pic 18: carrying nut

7.5 Examine of the stability of the automotive lift

- Examine the dowels with a torque key as described by the dowel manufacturer. Observe the declaration of the dowel manufacturer.

8. Installation and Initiation



pic 18:

8.1 Regulations

- The installation of the lift is performed by trained technicians of the manufacturer or one of its distribution partners. If the operator can provide trained mechanics, he or she can install the lift by him or herself. The installation has to be done according to this regulation.
- Installing the standard-automotive lift in a hazardous location or a washing bay is not allowed.
- Before installation a sufficient foundation must be constructed. If the foundation is already constructed then proof that the foundation conforms to the standard is required. A level foundation for the installation is required. The foundations must be based in a frost resistance depth, both outdoors and indoors in a position where the installer believes there is no chance of frost.
- An standard electrical supply 3~/N+PE, 400 V, 50 Hz must be provided. Observe the electrical power supply of your country.
The supply line must be protected with a time-lag fuse 32 Ampere time lag (VDE0100 German regulation). The minimum diameter amounts to 2.5 mm².
- All cable ducts must be equipped with protective coverings to prevent accidents.
- After assembly of the lift, the protective grounding of the lift must be examined after International Electrotechnical Commission (IEC) guidelines (60364-6-61) before first start-up by operators. Also an insulation resistance examination is recommended.

8.1.1 Erection and doweling of the lift




Before installation the lift, secure the installation area to prevent access to unauthorised persons. Use devices such as cranes, fork lift trucks and supports to transport the lift and avoid accidents.


Before installation of the lift create a sufficiently concrete by customer. The operator is responsible for the installation place. A concrete with a quality of minimum C20/25 and a thickness without tiles and floor pavement is necessary (thickness => see the foundation drawing).

We point out the minimum requirement of the foundation in our plans. The condition of the local realities (for example: the ground under the foundation) does not lie in our responsibility. The execution of the installation situation must be individually specified by the planning architect or by the engineer engaged in statically calculations in the special case.

In case of doubt a test boring has to be performed and a dowel is to set in. Afterwards the dowel is tighten with a torque which is described of the dowel manufacturer.
If there are defectives (cracks or hairline cracks) in the zone of influence Ø200 mm, the foundation cannot be used to install the lift on it.



A foundation must be constructed in accordance with the data sheet "foundation plan". It must be paid attention of an even installation place of the lift because of a straight contact between lift and concrete floor.



pic 19: dowel position

1: column

2: base plate

3: dowel

- Concrete has long chemical perspiration, which favour the corrosion at the base plates. We recommended to provide the surface with a 2 components Epoxitharz floor coating, before fastening the lift.
- Bore the holes to position the dowels through the bore holes of the base plates (pic.20). Clean the holes with pressure air. Insert the dowels. The lift manufacturer recommend e.g. Liebig, Hilti, Fischer safety dowels or equal dowels of other manufacturer (with licence) but observe the regulation. (bore hole, torque....). Before doweling check the concrete floor with quality C20/25 if the concrete floor goes to the top edge of the floor. In this case the dowels have to be chosen in according to the description (Dowels without tiles, floor pavement). If the ground is covered with floor tiles, the dowels have to be chosen according to description (Dowels with tiles, floor pavement). Observe the table of the Dowel manufacturer, too.
- Examine the lining up of the columns with spirit level.
- If necessary put thin metal sheets between the base plate and the floor until the lift is in the correct vertical position and the contact between the base plate and the floor is available.
- Tighten the dowels with the dynamometric key. Observe the regulations of the dowel manufacturer.



Each dowel must be tightened with the demanded torque. Otherwise the normal function of the lift can not guaranteed.

- If the dowel is tightened with the demanded torque, the curved washer lies flat on the base plate. A safe dowel connection is guaranteed.

8.2 Initiation



Before the initiation a security check must be carried out. Therefore use the form: First security check.

If the lift is installed by a competent person, he or she is to perform the security check. If the operator installs the lift by him or herself, he or she must instruct a competent person to perform the security check.

The competent confirms the faultless function of the lift in the installation record and the form for the security check and authorises the use of the lift.



Please send the completed installation record to the manufacturer after installation.

8.3 Change of lift location

If the place of installation shall be changed, the new place has to be prepared in according to the regulations of the first installation. The changing should be performed in accordance with the following points:

- Lift or lower the carriage to medium height.
- Take away current supply from the lift.
- If necessary remove the ascending pipe and the traverse.
- Remove the cover of the lift.

- Disconnect the plugs.
- Loosen the dowels.
- Dismount the columns.
- Dismount the crossbeams.
- Transport the lift to the new installation place.
- Install the lift in accordance with chapter 8 "Installation and Initiation"




Use new dowels, the used dowels can not be used anymore.

A security check must be performed before re initiation by a competent person. Use the sheet "Regular security check".

8.4 Key in the reference point with the keyboard

After mounting and adjusting of the lift and platforms, raise the lift on a comfortable working height. (e.g. approx. 1250mm)


Position the arrow sticker at the lifting carriage and the column after entering of the new reference point. (see the drawing)



Function button:

<*> (star): back to the position display
<#> (lozenge): confirm button

- Measure the distance (X) between the lower edge of the lifting carriage and the upper side of the base plate. Carry out the procedure at all four columns.



- The smallest measure will be used later as the new reference point height.

Login to the service operation:


- (#) Press it at the keyboard,
- Enter the numbers 1,2,3,4.
After the correct entering, it will be change into the main menu..
- Press the (*) button until the Display shows „Referenzpunkt“.
- A menu item is selected with <>.
- Then press the button (#).The adjusted value will be displayed.
- Enter now the smallest 4-digit value in the keyboard. (e.g. 1237)
- Then press the button (#).The entered value is confirmed.
- Press the button (*) until the position display (start position).

Passwort

— — — —

1	xxxx
2	xxxx
3	xxxx
4	xxxx

- Before lifting or lowering the lift position the sticker.



Unequal height after an lifting procedure „Referenzfahrt“

If you find after an lifting procedure a unequal position of one or more marker arrows, the unequal height must be corrected manually.

Switch off the main switch before the different columns will be adjusted.

Remove the above cover of the affected column. Turn the spindle with a suitable tool until the arrows are again on the same height. Repeat the procedure if necessary at the other columns. Switch on the main switch if the adjusting is finished.

9. Security check

The security check is necessary to guarantee the safety of the lift during use. It has to be performed in the following cases:

1. Before the initial operation, after the first installation.
Use the form “First security check before initiation”
2. In regular intervals after the initial operation, at least annually.
Use the form “Regular security check at least annually”
3. Every time the construction of that particular lift has been changed.
Use the form “Extraordinary security check”




The first and the regular security check must be performed by a competent person. It is also recommended to carry out a service on the lift at this time.



After the construction of the lift has been changed (changing the lifting height or capacity for example) and after serious maintenance works (welding load bearing parts) an extraordinary security check must be performed by an expert.

This manual contains forms with a schedule for the security checks. Please us the appropriate forms for the security checks. The forms should remain in this manual after they have been filled out. A short description about special safety devices follows.

pic: Selection of Liebig-Dowels without tiles, floor pavement




Liebig dowels

Dowel typ	BM12-20/80/40
Drilling depth	a 100
Min. anchorage depth	b 80
Thickness of concrete	c min.160 (*)
Diameter of bore	d 20
Thickness of the lift-pieces	e 0-40
Quality of concrete	min.C20/25 with normal armouring
Number of bolts	24
Starting torque	70 Nm

() minimum thickness of concrete by using the mentioned dowels. Otherwise, observe the regulation of the foundation plan.*

It is possible to use equivalent dowels from another dowel manufacturer (with license) but observe their regulation.

pic: Selection of Liebig-Dowels with tiles, floor pavement




Liebig dowels

Dowel type	BM12-20/80/65	BM12-20/80/100	BM12-20/80/140
Drilling depth (mm)	a 100	100	100
Min. anchorage depth (mm)	b 80	80	80
Thickness of concrete (mm)	c min.160(*)	min.160(*)	min.160(*)
Diameter of bore (mm)	d 20	20	20
Thickness of the lift-pieces (mm)	e+f 40-65	65-100	100-140
Quality of concrete	min.C20/25 with normal armouring		
Number of bolts	24	24	24
Starting torque	70 Nm	70Nm	70Nm


() minimum thickness of concrete by using the mentioned dowels. Otherwise, observe the regulation of the foundation plan.*

It is possible to use equivalent dowels from another dowel manufacturer (with license) but observe their regulation.




fischer-dowel		4.50 SL ^f		
Dübel typ of dowel type de cheville		FH 15/50 B Bestellnr. 970265	FH 18 x 100/100 B Bestellnr. 972230	FH 24/100 B Bestellnr. 970267
Bohrtiefe drilling depth Profondeur de l'alésage	t _d	145	230	255
Mindestverankerungstiefe min.anchorage depth Profondeur minimale d'ancrage	h _{ef}	70	100	125
Betonstärke thickness of concrete Epaisseur du béton	c	siehe den aktuellen Fundamentplan see current foundation-diagram drawing voir le plan de fondation actuel		
Bohrerdurchmesser diameter of bore Diamètre de l'alésage	d ₀	15	18	24
Bauteildicke thickness of the lift-piece Epaisseur de la pièce	t _{fix}	0-50	0-100	0-100
Anzugsdrehmoment Nm turning moment moment d'une force	M _D	40	80	120
Gesamtlänge Total length Longueur totale	l	155	230	272
Gewinde Thread fil	M	M10	M12	M16
Stückzahl piece number nombre des pièces	a	4		
	b	8		
	c	10		
	d	12		
	e	16		
	f	24		
	g	14		


Montage



Es können auch gleichwertige Sicherheitsdübel anderer Hersteller (mit Zulassung) unter Beachtung deren Bestimmungen verwendet werden.
It is possible to use equivalent safety-dowels (with license) of other manufacturer but observe their regulations.
Des chevilles des autres marques (autorisées) peuvent aussi être choisies en respectant les directives du fabricant.



Hilti-Dübel						
Bodenbelag (Estrich, Fliesen)		ohne Bodenbelag without	ohne Bodenbelag without	mit Bodenbelag with	ohne Bodenbelag without	mit Bodenbelag with
Floor pavements (tiles)		HSL-3-G M10/40 Art.Nr.37197	HSL-3-G M12/50 Art.Nr.371800	HSL-3-G M12/100 Art.Nr.371831	HSL-3-G M16/50 Art.Nr.371803	HSL-3-G M16/100 Art.Nr.371832
Dübel typ of dowel type de cheville	h_1	90	105	105	125	125
Bohrtiefe drilling depth Profondeur de l'alésage	h_{ef}	70	80	80	100	100
Mindestverankerungstiefe min.anchorage depth Profondeur minimale dáncreage	c	siehe den aktuellen Fundamentplan see current foundation-diagram drawing vois le plan de fondation actuel				
Betonstärke thickness of concrete Epaisseur du béton	d_0	15	18	18	24	24
Bohrerdurchmesser diameter of bore Diamètre de l'alésage	t_{fix}	0-40	0-50	0-100	0-50	0-100
Bauteildicke thickness of the lift-piece Epaisseur de la pièce						
Anzugsdrehmoment Nm turning moment moment d'une force	T_{inst}	35	60	60	80	80
Gesamtlänge Total length Longueur totale	l	135	164	214	188	238
Gewinde Thread fil	M	10	12	12	16	16
Stückzahl piece number nombre des pièces	a			4		
	b			8		
	c			10		
	d			12		
	e			14		
	f			16		
	g			28		



Es können auch gleichwertige Sicherheitsdübel anderer Hersteller (mit Zulassung) unter Beachtung deren Bestimmungen verwendet werden.
It is possible to use equivalent safety-dowels (with license) of other manufacturer but observe their regulations.
Des chevilles des autres marques (autorisées) peuvent aussi être choisies en respectant les directives du fabricant.

First security check before installation

Fill out and leave in this manual Serial-number: _____

kind of check	all right	defect missing	veri-fication	remark
Type plate.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
short operating instruction at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker capacity at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker lubrication/maintenance plan.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Detailed operating instruction.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Automotive-lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Designation „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „equalisation“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function Display.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Electrical box.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function main switch.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Safety seeger ring at the bolts (carriage).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function CE-Stop + acoustic signal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition bolts and DU-bearings.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function drive on ramps.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function plugs at the Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>(only for wheel alignment).....
Condition colour.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Construction (deformation, cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Torque moment of screws and dowels	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Poly V-Belt.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function spindle centering.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Crossbeam & cable channel.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition of the covers	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Spindle and carrying nut.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition carrying nut wear pin.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition concrete (cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition electrical cables and plugs.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function lighting.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test with vehicle.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test „driving to the end position“	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function equalisation of the lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

(mark here applicable, in case of verification mark in addition to the first mark!)

Security check carried out:.....

Carried out the company:.....

Name, address of the competent:.....

Result of the Check:

- Initiation not permitted, verification necessary
- Initiation possible, repair failures until.....
- No failings, Initiation possible

.....
signature of the expert

.....
signature of the operator

If failures must be repaired:

Failures repaired at:

.....
signature of the operator

(Use another form for verification!)

Regular security check and maintenance


Fill out and leave in this manual

Serial-number: _____

kind of check	all right	defect missing	veri-fication	remark
Type plate.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
short operating instruction at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker capacity at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker lubrication/maintenance plan.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Detailed operating instruction.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Automotive-lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Designation „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „equalisation“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function Display.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Electrical box.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function main switch.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Safety seeger ring at the bolts (carriage).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function CE-Stop + acoustic signal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition bolts and DU-bearings.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function drive on ramps.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function plugs at the Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition colour.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Construction (deformation, cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Torque moment of screws and dowels	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Poly V-Belt.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function spindle centering.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Crossbeam & cable channel.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition of the covers	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Spindle and carrying nut.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition carrying nut wear pin.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition concrete (cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition electrical cables and plugs.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function lighting.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test with vehicle.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test „driving to the end position“	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function equalisation of the lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

(mark here applicable, in case of verification mark in addition to the first mark!)

Security check carried out:

Carried out the company:

Name, address of the competent:

Result of the Check:

- Initiation not permitted, verification necessary
- Initiation possible, repair failures until.....
- No failings, Initiation possible

 signature of the expert

 signature of the operator

If failures must be repaired:

Failures repaired at:

 signature of the operator

(Use another form for verification!)

Regular security check and maintenance


Fill out and leave in this manual

Serial-number: _____

kind of check	all right	defect missing	veri-fication	remark
Type plate.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
short operating instruction at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker capacity at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker lubrication/maintenance plan.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Detailed operating instruction.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Automotive-lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Designation „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „equalisation“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function Display.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Electrical box.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function main switch.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Safety seeger ring at the bolts (carriage).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function CE-Stop + acoustic signal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition bolts and DU-bearings.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function drive on ramps.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function plugs at the Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition colour.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Construction (deformation, cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Torque moment of screws and dowels	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Poly V-Belt.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function spindle centering.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Crossbeam & cable channel.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition of the covers	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Spindle and carrying nut.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition carrying nut wear pin.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition concrete (cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition electrical cables and plugs.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function lighting.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test with vehicle.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test „driving to the end position“	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function equalisation of the lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

(mark here applicable, in case of verification mark in addition to the first mark!)

Security check carried out:

Carried out the company:

Name, address of the competent:

Result of the Check:

- Initiation not permitted, verification necessary
- Initiation possible, repair failures until.....
- No failings, Initiation possible

 signature of the expert

 signature of the operator

If failures must be repaired:

Failures repaired at:

.....

(Use another form for verification!)

signature of the operator

Regular security check and maintenance


Fill out and leave in this manual

Serial-number: _____

kind of check	all right	defect missing	veri-fication	remark
Type plate.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
short operating instruction at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker capacity at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker lubrication/maintenance plan.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Detailed operating instruction.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Automotive-lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Designation „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „equalisation“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function Display.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Electrical box.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function main switch.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Safety seeger ring at the bolts (carriage).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function CE-Stop + acoustic signal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition bolts and DU-bearings.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function drive on ramps.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function plugs at the Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition colour.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Construction (deformation, cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Torque moment of screws and dowels	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Poly V-Belt.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function spindle centering.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Crossbeam & cable channel.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition of the covers	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Spindle and carrying nut.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition carrying nut wear pin.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition concrete (cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition electrical cables and plugs.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function lighting.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test with vehicle.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test „driving to the end position“	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function equalisation of the lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

(mark here applicable, in case of verification mark in addition to the first mark!)

Security check carried out:

Carried out the company:

Name, address of the competent:

Result of the Check:

- Initiation not permitted, verification necessary
- Initiation possible, repair failures until.....
- No failings, Initiation possible

 signature of the expert

 signature of the operator

If failures must be repaired:

Failures repaired at:

.....

(Use another form for verification!)

signature of the operator

Regular security check and maintenance


Fill out and leave in this manual

Serial-number: _____

kind of check	all right	defect missing	veri-fication	remark
Type plate.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
short operating instruction at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker capacity at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker lubrication/maintenance plan.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Detailed operating instruction.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Automotive-lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Designation „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „equalisation“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function Display.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Electrical box.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function main switch.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Safety seeger ring at the bolts (carriage).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function CE-Stop + acoustic signal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition bolts and DU-bearings.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function drive on ramps.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function plugs at the Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition colour.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Construction (deformation, cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Torque moment of screws and dowels	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Poly V-Belt.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function spindle centering.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Crossbeam & cable channel.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition of the covers	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Spindle and carrying nut.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition carrying nut wear pin.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition concrete (cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition electrical cables and plugs.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function lighting.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test with vehicle.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test „driving to the end position“	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function equalisation of the lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

(mark here applicable, in case of verification mark in addition to the first mark!)

Security check carried out:

Carried out the company:

Name, address of the competent:

Result of the Check:

- Initiation not permitted, verification necessary
- Initiation possible, repair failures until.....
- No failings, Initiation possible

 signature of the expert

 signature of the operator

If failures must be repaired:

Failures repaired at:

.....

(Use another form for verification!)

signature of the operator

Regular security check and maintenance

Fill out and leave in this manual Serial-number: _____

kind of check	all right	defect missing	veri-fication	remark
Type plate.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
short operating instruction at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker capacity at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker lubrication/maintenance plan.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Detailed operating instruction.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Automotive-lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Designation „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „equalisation“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function Display.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Electrical box.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function main switch.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Safety seeger ring at the bolts (carriage).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function CE-Stop + acoustic signal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition bolts and DU-bearings.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function drive on ramps.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function plugs at the Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>(only for wheel alignment).....
Condition colour.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Construction (deformation, cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Torque moment of screws and dowels	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Poly V-Belt.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function spindle centering.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Crossbeam & cable channel.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition of the covers	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Spindle and carrying nut.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition carrying nut wear pin.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition concrete (cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition electrical cables and plugs.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function lighting.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test with vehicle.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test „driving to the end position“	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function equalisation of the lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

(mark here applicable, in case of verification mark in addition to the first mark!)

Security check carried out:.....

Carried out the company:.....

Name, address of the competent:.....

Result of the Check:

- Initiation not permitted, verification necessary
- Initiation possible, repair failures until.....
- No failings, Initiation possible

.....
signature of the expert

.....
signature of the operator

If failures must be repaired:

Failures repaired at:

.....
signature of the operator

(Use another form for verification!)

Regular security check and maintenance

Fill out and leave in this manual Serial-number: _____

kind of check	all right	defect missing	veri-fication	remark
Type plate.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
short operating instruction at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker capacity at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker lubrication/maintenance plan.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Detailed operating instruction.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Automotive-lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Designation „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „equalisation“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function Display.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Electrical box.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function main switch.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Safety seeger ring at the bolts (carriage).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function CE-Stop + acoustic signal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition bolts and DU-bearings.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function drive on ramps.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function plugs at the Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	(only for wheel alignment).....
Condition colour.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Construction (deformation, cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Torque moment of screws and dowels	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Poly V-Belt.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function spindle centering.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Crossbeam & cable channel.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition of the covers	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Spindle and carrying nut.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition carrying nut wear pin.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition concrete (cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition electrical cables and plugs.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function lighting.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test with vehicle.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test „driving to the end position“	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function equalisation of the lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

(mark here applicable, in case of verification mark in addition to the first mark!)

Security check carried out:.....

Carried out the company:.....

Name, address of the competent:.....

Result of the Check:

- Initiation not permitted, verification necessary
- Initiation possible, repair failures until.....
- No failings, Initiation possible

.....
signature of the expert

.....
signature of the operator

If failures must be repaired:

Failures repaired at:

.....
signature of the operator

(Use another form for verification!)

Regular security check and maintenance

Fill out and leave in this manual Serial-number: _____

kind of check	all right	defect missing	veri-fication	remark
Type plate.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
short operating instruction at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker capacity at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker lubrication/maintenance plan.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Detailed operating instruction.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Automotive-lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Designation „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „equalisation“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function Display.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Electrical box.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function main switch.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Safety seeger ring at the bolts (carriage).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function CE-Stop + acoustic signal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition bolts and DU-bearings.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function drive on ramps.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function plugs at the Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>(only for wheel alignment).....
Condition colour.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Construction (deformation, cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Torque moment of screws and dowels	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Poly V-Belt.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function spindle centering.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Crossbeam & cable channel.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition of the covers	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Spindle and carrying nut.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition carrying nut wear pin.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition concrete (cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition electrical cables and plugs.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function lighting.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test with vehicle.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test „driving to the end position“	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function equalisation of the lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

(mark here applicable, in case of verification mark in addition to the first mark!)

Security check carried out:.....

Carried out the company:.....

Name, address of the competent:.....

Result of the Check:

- Initiation not permitted, verification necessary
- Initiation possible, repair failures until.....
- No failings, Initiation possible

.....
signature of the expert

.....
signature of the operator

If failures must be repaired:

Failures repaired at:

.....
signature of the operator

(Use another form for verification!)

Extraordinary security check

Fill out and leave in this manual Serial-number: _____

kind of check	all right	defect missing	veri-fication	remark
Type plate.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
short operating instruction at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker capacity at the column.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
sticker lubrication/maintenance plan.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Detailed operating instruction.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Automotive-lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Designation „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „lifting/lowering“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function button „equalisation“.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function Display.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Electrical box.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function main switch.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Safety seeger ring at the bolts (carriage).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function CE-Stop + acoustic signal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition bolts and DU-bearings.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function drive on ramps.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function plugs at the Platform.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>(only for wheel alignment).....
Condition colour.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Construction (deformation, cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Torque moment of screws and dowels	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Poly V-Belt.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition, Function spindle centering.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Crossbeam & cable channel.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition of the covers	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition Spindle and carrying nut.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition carrying nut wear pin.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition concrete (cracking).....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Condition electrical cables and plugs.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function lighting.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test with vehicle.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function test „driving to the end position“	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Function equalisation of the lift.....	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

(mark here applicable, in case of verification mark in addition to the first mark!)

Security check carried out:.....

Carried out the company:.....

Name, address of the competent:.....

Result of the Check:

- Initiation not permitted, verification necessary
- Initiation possible, repair failures until.....
- No failings, Initiation possible

.....
signature of the expert

.....
signature of the operator

If failures must be repaired:

Failures repaired at:

.....
signature of the operator

(Use another form for verification!)

Inhaltsverzeichnis


Seite	Seitenbenennung	Seitenzusatzfeld	Datum	Bearb.	X
1	Deckblatt		16.11.2009	BOE	
2	Inhaltsverzeichnis		23.02.2010	BOE	X
3	Aenderung		16.11.2009	BOE	
4	Hauptstrom		23.02.2010	BOE	
5	Hauptstrom		18.02.2010	BOE	
6	Frei		19.02.2010	BOE	
7	Bedientasten		18.02.2010	BOE	
8	Achsencontroller		23.02.2010	BOE	
9	Säulenansteuierung		18.02.2010	BOE	
10	FU		20.11.2009	BOE	
11	Frei		19.02.2010	BOE	
12	-X1		16.11.2009	BOE	X
13	-X2		16.11.2009	BOE	X
14	-XHS1..2		16.11.2009	BOE	X
15	-XHS2..2		16.11.2009	BOE	X
16	-XHS3..2		16.11.2009	BOE	X
17	-XHS4..2		16.11.2009	BOE	X
18	-XST1		16.11.2009	BOE	X
19	-XST2		16.11.2009	BOE	X
20	-XST3		16.11.2009	BOE	X
21	-XST4		16.11.2009	BOE	X
22	Stückliste		23.02.2010	BOE	X
23	Stückliste		23.02.2010	BOE	X
24	Stückliste		23.02.2010	BOE	X


1


65


Hussbaum Hebe-technik GmbH & Co KG
Königstrasse 24
D-7047 Stuttgart - Beauftragt: Dr. H. Hussbaum
Tel. 0711/530187 Fax. 0711/530187
Ers. d.
Urspr.
Name Norm
Bearb. BIE
Datum 20.06.13
Datum 10.08.10


ÄNDERUNGS-INFORMATIONEN

















0	1	2	3	4	5	6	7	8	9	10
---	---	---	---	---	---	---	---	---	---	----

2

5

6

8

2

11

13

24 61
12

81

10

+

1

- X1

1

1

v

schemas

X SL A

4. X

8787

卷之二
七

Metatechnik
Kohler Straße
1 Nohl - Boden
0899-0 Fax:

d.

baum Hebe
ke
0 -77694
491017853 /
Ers.

Mus 1

Ers. f.

5

5

Ursu

06.13

atum 10.
earb. BOE
epr. 20.
orm

D	B	G	H
			Name _____

Datum

änderung

4

12

13

15

14

16

15

-XHSH.2

WUPKMO20 / 22.04.1998

Klemmeplan

16

WUPFRH020 / 22.04.1998

Klemmeplan

1

	0	1	2	3	4	5	6	7	8	9
Seite/Pfad										
MPKMH020 / 22.04.1996										
Kabelname										
Kabeltyp										
Ölfilter Classic										
Klemmen-										
Anschluß										
Ziel-										
bezeichnung										
Klemmen-										
Symbole										
Brücken										
Klemmen-										
nummer										
Anschluß										
Ziel-										
bezeichnung										
Kabelname										
Kabeltyp										
-XST 2										
Lösitanweisung										
Funktionsblock										
Motor Sauer 2										
Steckdose Energieset										
Klemmenplan										
Änderung	Datum	Name	Norm	Urspr.	Ers. f.					
18										
19										
20										

	0	1	2	3	4	5	6	7	8	9
Seite/Pfad										
Kabel										
MUPK4020 / 22.04.1996										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Klammer-Symbol										
Brücken										
Klammennummer										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										
Anschluß										
Zielbezeichnung										
Kabelname										
Kabeltyp										

20

22

Stückliste Bill of materials

Bauteilbezeichnung Component design.	Menge Amount	Bezeichnung Designation	Typen nummer Model number	Lieferant Supplier	Artikelnummer Article number
-J	1	E-Bon. Beleucht. 300x1200x155	810405-0260-B08	Krauth technology	810405-0260-B08
-J	1	Hantagelatte ungelocht 300x1200	810405-0260	Krauth technology	810405-0260
-H0	1	Hauptsch. Not. Raus 3P 40A - 11kW	812511-6_1050	Herz GmbH	920375
-X1	4	Rahmenlampe H 16/12 schraub-schraub	H 10/12	Entelec	92074
-X1	1	Schutzleiterklammer H 16/12 P schraub-schraub	H 10/12 P	Entelec	920844
-X1	8	Rahmenlampe D 9/8 R00 grau schraub-schraub	0 6/8 R00	Entelec	920533
-X1	8	Schutzleiterkl. D 6/8 P R00 schraub-schraub	0 6/8 P R00	Entelec	920534
-X1	6	Rahmenlampe 0 1,5/6 R00 grau schraub-schraub	0 1,5/6 R00	Entelec	920185
-X1	3	Schutzleiterkl. D 2,5/6 P R00 schraub-schraub	0 2,5/6 P R00	Entelec	ENT 16218822
-X1	2	Schutzleiterklammer	H 2,5/5 PI	Entelec	
-MF	1	Blanko Schild	EF510 5x10	Entelec	ENT 23100007
-MF	1	Sicherungsautomat 3 pol. 16 A Typ K	EF63-116	General Electric	928384
-ST1	1	Steckergehäuse 6 polig ku	05-0-181906-0	RiP	920327
-ST1	6	Flachsteckhülle Stecker 6,3mm	05547 123 111	RiP	920328
-ST1	6	Flachsteckhülle Büchse 6,3mm CÜZN ohne 150	05547 123 211	RiP	920329
-ST1	1	Buchsteckhähnchen 6 polig ku	2 105 510290233	RiP	920330
-NH	1	Drehstrommotor 1,5kW/4,7R 50Hz SL	#7HU10-239	Hannina GmbH	920290
-ST2	1	Steckergehäuse 6 polig ku	05-0-181906-0	RiP	920327
-ST2	6	Flachsteckhülle Stecker 6,3mm	05547 123 111	RiP	920328
-ST2	6	Flachsteckhülle Büchse 6,3mm CÜZN ohne 150	05547 123 211	RiP	920329
-ST2	1	Buchsteckhähnchen 6 polig ku	2 105 510290233	RiP	920330
-NH	1	Drehstromotor 1,5kW/4,7R 50Hz SL	#7HU10-239	Hannina GmbH	920290
-EF	1	Sicherungsautomat 3 pol. 16 A Typ K	EF63-116	General Electric	928384
-ST3	1	Steckergehäuse 6 polig ku	05-0-181906-0	RiP	920327
-ST3	6	Flachsteckhülle Stecker 6,3mm	05547 123 111	RiP	920328
-ST3	6	Flachsteckhülle Büchse 6,3mm CÜZN ohne 150	05547 123 211	RiP	920329
-ST3	1	Buchsteckhähnchen 6 polig ku	2 105 510290233	RiP	920330
-NH	1	Drehstromotor 1,5kW/4,7R 50Hz SL	#7HU10-239	Hannina GmbH	920290
-ST4	1	Steckergehäuse 6 polig ku	05-0-181906-0	RiP	920327
-ST4	6	Flachsteckhülle Stecker 6,3mm	05547 123 111	RiP	920328
-ST4	6	Flachsteckhülle Büchse 6,3mm CÜZN ohne 150	05547 123 211	RiP	920329
-ST4	1	Buchsteckhähnchen 6 polig ku	2 105 510290233	RiP	920330
-NH	1	Drehstrommotor 1,5kW/4,7R 50Hz SL	#7HU10-239	Hannina GmbH	920290
-ST4	1	Fansicherung	EF63-116	General Electric	928384
-EF	1	Fansicherungshalter 5x20 mm	05547 123 111	RiP	920327
-EF	1	Fansicherung aus 1 * Steckdose 1= Luftanschluss	05547 123 111	RiP	920328
-EF	1	Fansicherung aus 1 * Steckdose 1= Luftanschluss	05547 123 211	RiP	920329
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920330
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920331
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920332
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920333
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920334
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920335
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920336
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920337
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920338
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920339
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920340
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920341
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920342
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920343
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920344
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920345
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920346
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920347
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920348
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920349
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920350
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920351
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920352
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920353
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920354
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920355
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920356
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920357
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920358
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920359
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920360
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920361
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920362
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920363
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920364
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920365
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920366
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920367
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920368
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920369
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920370
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920371
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920372
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920373
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920374
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920375
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920376
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920377
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920378
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920379
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920380
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920381
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920382
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920383
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920384
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920385
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920386
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920387
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920388
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920389
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920390
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920391
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920392
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920393
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920394
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920395
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920396
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920397
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920398
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920399
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920400
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920401
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920402
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920403
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920404
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920405
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920406
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920407
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920408
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920409
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920410
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920411
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920412
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920413
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920414
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920415
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920416
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920417
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920418
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920419
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920420
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920421
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920422
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920423
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920424
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920425
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920426
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920427
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920428
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920429
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920430
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920431
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920432
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920433
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920434
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920435
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920436
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920437
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920438
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920439
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920440
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920441
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920442
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920443
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920444
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920445
-EF	1	Fansicherungshalter 5x20 mm	05547 123 211	RiP	920446
-EF	1	Fansicherungshalter 5x20 mm	055		

Stückliste Bill of materials

Stückliste Bill of materials

22


Stückliste Bill of materials

Bauteilbezeichnung Component design.	Menge Amount	Bezeichnung Designation	Typen nummer Model number	Lieferant Supplier	Artikelnummer Article number
-NH 52 2	1	Steckverb. Gerätestecker Ku 6 pol	STECKVERBINDER	RS Component	900919
-NH 52 2	6	Schaftleinsatz für Gerätestecker	SCHLEIFTEILSATZ	Spiele GmbH	901330
-NH 52 2	6	Buchseleinsatz für Gerätestecker	BUCHSELEINSATZ	Spiele GmbH	901331
-BK 2	1	INDUSTRIEPLAETSES 4W4 Wechsler	2741	BTR	90207
-BK 2	1	Industrieralessochel für 4 Wechsler	110178	BTR	90381
-BB 3	1	Drehheber für SL Poti Rad	4505LDRHEBER	Nussbaum	4505LDRHEBER
-NH 53 2	1	Steckverb. Gerätestecker Ku 6 pol	STECKVERBINDER	RS Component	900918
-NH 53 2	6	Schaftleinsatz für Gerätestecker Ku 6 pol	SCHLEIFTEILSATZ	RS Component	900919
-NH 53 2	6	Buchseleinsatz für Gerätestecker	BUCHSELEINSATZ	Spiele GmbH	901330
-NH 53 2	6	Buchseleinsatz für Gerätestecker	BUCHSELEINSATZ	Spiele GmbH	901331
-BB 4	1	Drehheber für SL Poti Rad	4505LDRHEBER	Nussbaum	4505LDRHEBER
-NH 54 2	1	Steckverb. Gerätestecker Ku 6 pol	STECKVERBINDER	RS Component	900918
-NH 54 2	6	Schaftleinsatz für Gerätestecker	SCHLEIFTEILSATZ	Spiele GmbH	901330
-NH 54 2	6	Buchseleinsatz für Gerätestecker	BUCHSELEINSATZ	Spiele GmbH	901331
-BH 2	1	Disposition austauschbarer Signalebner	BIP 238	Dalton Components	900331
-BB 3	1	Folientaktatatur für RIC 4000	1113-2903	Nussbaum	900265
-BB 3	1	Tastaturtabelle RIC Controller	990875	Nussbaum	900875
-BH 2	1	Display für RIC 4000	DEH16181 ST-LY/L	Nussbaum	900257
-BR 2	1	Disp.rahmen groß . mit Tastatur	990090	Nussbaum	900630
-BR 2	1	Disp.kabel Controller	900874	Nussbaum	900874
-BK 1	1	Hauptschutz, DILH15-01, 24VDC, INC.	DILH15-01(24VDC)	Hoeller	903516
-BK 2	1	Hauptschutz, DILH15-01, 24VDC, INC.	DILH15-01(24VDC)	Hoeller	903516
-BK 3	1	Hauptschutz, DILH15-01, 24VDC, INC.	DILH15-01(24VDC)	Hoeller	903516
-BK 4	1	Hauptschutz, DILH15-01, 24VDC, INC.	DILH15-01(24VDC)	Hoeller	903516
-H-4/1	1	Steuerleitung mit numerierten Fäden und	OLFLEX GECKHIT	Kabelflex	900838
-H-4/2	1	Steuerleitung mit numerierten Fäden und	OLFLEX GECKHIT	Kabelflex	900838
-H-5/1	1	Steuerleitung mit numerierten Fäden und	OLFLEX GECKHIT	Kabelflex	900838
-H-5/2	1	Steuerleitung mit numerierten Fäden und	OLFLEX GECKHIT	Kabelflex	900838
-H-8/1	1	Steuerleitung 7x0,5 mm² geschirmt	PVC STEUERLEITUNG LY/C	Kabel Wachter GmbH & Co KG	901336
-H-8/2	1	Steuerleitung 7x0,5 mm² geschirmt	PVC STEUERLEITUNG LY/C	Kabel Wachter GmbH & Co KG	901336
-H-8/3	1	Steuerleitung 7x0,5 mm² geschirmt	PVC STEUERLEITUNG LY/C	Kabel Wachter GmbH & Co KG	901336
-H-8/4	1	Steuerleitung 7x0,5 mm² geschirmt	PVC STEUERLEITUNG LY/C	Kabel Wachter GmbH & Co KG	901336

Spare parts

Lfd. Nr.	Nenge Nr.	Zeichnungs-Nr.:	Benennung
1	2	MKS-VL-HR	-
2	2	MKS-VR-HL	-
3	1	450SL44211	Aufdeckung kpl. l.
4	1	020UK00025	Achssheber klappt
5	2	450SL28930	Auf Fahrername kpl.
6	2	450SL08820	Auf Fahrername SLR kpl.
7	1	450SL05149	Bediensäule v. l.
8	1	450SL47501	Kabeikonol. kpl. Typ 02
9	1	450SL05118	Sägele kpl. h. l.
10	1	450SL05119	Sägele kpl. v. r.
11	1	450SL05148	Sägele kpl. h. r.
12	1	450SL28751	Schiene 11. kpl.
13	1	450SL28701	Schiene re. kpl.
14	1	450SL06240	Troststück hinten
15	1	450SL06341	Troststück vorne
16	2	450SL28963	Überrollbügel Schw.
17	16	97991-M12X25	SENKSHAFTE

Gültig auch für 4.55 SL



Rasen ohne Toleranzgrenzen		Messstab 1:025		Gewicht: 20991.339g	
DIN ISO 2768 M4		Werkstoff / Holzbezug		 - i -	
		Bearb.	Datum	Name	Bemerkung
		(gepr.)	12.03.10	rrn	
		Norm			
		450SL kp. / Schienenl. 565019			
		Zeichnungsnr. 450SL20020		Blatt 1 von 2	
Nr.	Aenderung	Datum	Name/ursp.	Ersatz fuer: Rasen	