



SPRINTER NT

3500 KG

360°
Access



NT technology
from Nussbaum

Flexible loading platforms:

The ramps can be locked and unlocked to adjust the platform length to long or short vehicles.



Flexible width + length:

In addition to the fold-out extensions and the flexible set-up width, the SPRINTER NT X-Tend features extendable extensions.

The high-performance, low-noise **sub-oil unit** ensures smooth running and short lifting and lowering times.

THE LOW-RISE SOLUTION

- For installation above a pit or for floor-level installation
- The powerful sub-oil power unit guarantees short lifting and lowering times
- Fully hydraulic system with no pneumatic components on the lift
- No fixed connection between the platforms
- The anti-slip platforms are galvanised and the access ramps can be locked manually
- Low-rise scissor lift with direct pick-up
- Robust steel construction
- Covers most of your workshop activities

LIFT EVEN HEAVY VEHICLES UP TO 3.5 T

Covers most of your repair shop activities

The SPRINTER NT is an efficient solution for tire service, painting, body work and more.

360° access brings you a vast range of possibilities. The SPRINTER NT can be installed either above a service pit or at ground level, ensuring optimum working comfort.

Reliable hydraulic system

The lift is equipped with two independent hydraulic systems, each featuring two cylinders operating in a master–slave (command–sequence) system, ensuring precise, safe, and smooth movement.

The powerful, low-noise sub-oil unit with push-button operation ensures short lifting and lowering times.

The SPRINTER NT requires neither electronic synchronisation monitoring nor electronic limit switches.

This guarantees maximum reliability.

FAST AND VERSATILE

MODEL	3500	3500 X-Tend
Lifting capacity (kg)	3500	3500
Lifting / lowering time approx. (sec)	15	15
Lifting height (mm)	970	970
Drive-on height (mm)	102	102
Total width (mm)	1800	1880
Platform width (mm)	450	530
Platform length (mm)	1400-2007	1550-2320
Power supply (V / Hz / A)	400/50/16	400/50/16
Motor (kW)	3	3



Can be installed above a work pit or at floor level for optimum working comfort




Fire galvanization of scissors and base plate for corrosive environment

ACCESSORIES



Polymer pads 50x150x340 mm (included)



Polymer pads 100x150x340 mm



Tuning ramps



Pyramid pads

More accessories available